

Power: Quick Specs



Overview

The PM12018-01 PDU provides single phase power distribution utilizing a combination of (18) NEMA 5-20 outlets. Local current (Amp) metering is achieved via industry leading "True RMS" digital ammeter. Mounting is achieved in seconds using included tool-less mounting buttons.



Model: PM12018-01

- Product Family:
- Basic
 - Metered
 - Monitored (IP Access)
 - Switched (IP Control)

| Input Ratings | |
|--|------------------------|
| Voltage | 120V 60/50Hz |
| Amps | 20 Amps |
| Breakers | N/A |
| Meters on unit (amps) | 1 "True RMS" Ammeter |
| Input Plug/Cord | NEMA L5-20P / 10' cord |
| Output Ratings | |
| Voltage | 120V 60/50Hz |
| Outlets (Total) | (18) NEMA 5-20R |
| Outlets per phase | (18) NEMA 5-20R |
| Load Segment Per Phase | 20A |
| Total Power (kW) | 1.9kW de-rated |
| Physical | |
| Form Factor | Vertical - Zero U |
| Height | 29.5" |
| Width | 1.72" |
| Depth | 1.72" |
| Weight | 12lbs. |
| Regulatory | |
| UL60950-1, CSA22.2 No. 60950-1, EN60950-1 FCC Class A Part 15 | |

| Featured Options | |
|---------------------------------------|----|
| IP Receptacle Control (on/off/reboot) | No |
| IP Port Metering (amps@receptacle) | No |
| IP Environmental Monitoring | No |

