


# Power: Quick Specs



## Overview

The PM13018-01 PDU provides single phase power distribution utilizing a combination of (16) NEMA 5-20 outlets. Local current metering is achieved via industry leading "True RMS" digital ammeter. Mounting is achieved in seconds using included tool-less mounting buttons.



## Model: PM13016-01

Product Family:  Basic  
 Metered  
 Monitored (IP Access)  
 Switched (IP Control)

Input Ratings	
Voltage	100-120V 60/50Hz
Amps	30 Amps
Breakers	(2) UL 489, 20A
Meters on unit (amps)	1 "True RMS" Ammeter
Input Plug/Cord	NEMA L5-30P / 10' Cord
Output Ratings	
Voltage	100-120V 60/50Hz
Outlets (Total)	(16) NEMA 5-20
Outlets per branch	(8) NEMA 5-20
Load Segment Per Branch	20A
Total Power (kW)	2.8kW de-rated
Physical	
Form Factor	Vertical - Zero U
Height	29.5"
Width	2.18"
Depth	1.72"(Outlets) 3.5"(Breakers)
Weight	15lbs.
Regulatory	
UL60950-1, CSA22.2 No. 60950-1, EN60950-1 FCC Class A Part 15	

Featured Options	
IP Receptacle Control (on/off/reboot)	No
IP Port Metering (amps@receptacle)	No
IP Environmental Monitoring	No

