

# Power: Quick Specs



## Overview

The PM23024-02 PDU provides single phase power distribution utilizing a combination of (20) IEC C13 & (4) IEC C19 outlets. Local current metering is achieved via industry leading "True RMS" digital ammeter. Mounting is achieved in seconds using included tool-less mounting buttons.



## Model: PM23024-02

- Product Family:
- Basic
  - Metered
  - Monitored (IP Access)
  - Switched (IP Control)

| Input Ratings  |                                  |
|--|----------------------------------|
| Voltage  | 208V 60/50Hz                     |
| Amps   | 30 Amps                          |
| Breakers   | (2) UL 489 20A                   |
| Meters on unit (amps)  | (1) "True RMS" Ammeter           |
| Input Plug/Cord  | NEMA L6-30P / 10' Cord           |
| Output Ratings   |                                  |
| Voltage  | 208V 60/50Hz                     |
| Outlets (Total)  | (20) IEC C13 (4) IEC C19         |
| Outlets per branch   | (10) IEC C13 (2) IEC C19         |
| Load Segment Per Branch  | 20A                              |
| Total Power (kW)   | 4.9kW de-rated                   |
| Physical   |                                  |
| Form Factor  | Vertical - Zero U                |
| Height   | 66.5"                            |
| Width  | 2.18"                            |
| Depth  | 1.72"(Outlets)<br>3.5"(Breakers) |
| Weight   | 15lbs.                           |
| Regulatory   |                                  |
| UL60950-1, CSA22.2 No. 60950-1, EN60950-1<br>FCC Class A Part 15 |                                  |

| Featured Options                      |    |
|---------------------------------------|----|
| IP Receptacle Control (on/off/reboot) | No |
| IP Port Metering (amps@receptacle)    | No |
| IP Environmental Monitoring           | No |

